



F13 - 14 x 50cy mL		
Carbon Fiber Centrifuge Rotor		
RPM	MAX RCF	k factor
13000	28960	1499
12500	26775	1621
12000	24676	1759
11500	22662	1915
11000	20735	2093
10500	18892	2298
10000	17136	2533
9500	15465	2807
9000	13880	3127
8500	12381	3506
8000	10967	3958
7500	9639	4503
7000	8397	5169
6500	7240	5995
6000	6169	7036
5500	5184	8374
5000	4284	10132
4500	3470	12509
4000	2742	15831
3500	2099	20678
3000	1542	28145
2500	1071	40528
2000	685	63326
1500	386	112579
1000	171	253303
500	43	1013212

422 Aldo Avenue, Santa Clara, CA. 95054-2301
800.784.3843 - Fax 408.988.1196
www.piramoon.com

- Limited Lifetime Warranty!
- Corrosion free
- Up to 60% lighter than metallic equivalents
- Highly resistant to radiolabel contamination
- Compatible with all popular floor model centrifuges.
- No need for derating after years of use
- Fully autoclavable
- Superior insulating properties, making chilling unnecessary
- Competitively priced at or below the cost of conventional metallic rotors

Offering the rewards of 40 years of aerospace R&D to scientists and researchers everywhere. Not only is carbon fiber at the cutting edge of technology, it is also the most sensible and safe alternative to the standard aluminum and titanium alloys used today for all centrifugation rotors. With properties matching those of steel, but without the negative attributes, carbon fiber is leagues ahead of metal in regards to strength, weight, and malleability. Please contact FIBERLite for further product information.